NSN 4720-01-439-5506

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-439-5506 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.620 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 1.090 inches **Minimum Inside Bending Radius:** 8.000 inches **End Application:** 2320-01-344-9887 **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 14500.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and 2nd layer braided steel wire and outer layer spirally wrapped rubber fabric **Maximum Operating Pressure:** 3250.0 pounds per square inch **Thread Size:** 0.875 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 6500.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 57.000 inches **Thread Series Designator:**

N/a

Unf 1st end Shelf Life:

NSN 4720-01-439-5506

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0