Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-439-6680

Cross Sectional Shape:
Round
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
0.500 inches
Minimum Inside Bending Radius:
2.500 inches
Quick Disconnect Size:
0.250 inches 1st end
End Application:
Used on weapon system torpedo, adcap 48
Connection Style:
Push (internal) 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Unthreaded external tube 2nd end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and outer layer molded rubber, synthetic
Maximum Operating Pressure:
250.0 pounds per square inch
Hydrostatic Test Pressure:
500.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
12.000 inches excluding end fittings
Outside Diameter Tube Accommodated:
0.500 inches 2nd end
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No

NSN 4720-01-439-6680

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

