NSN 4720-01-439-7329

Nonmetallic Hose Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4720-01-439-7329 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response **Outside Diameter:** 0.500 inches **Minimum Inside Bending Radius:** 2.500 inches **Quick Disconnect Size:** 0.250 inches 2nd end **End Application:** Used on weapon system torpedo, adcap 48 **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 1000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided textile yarn and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 250.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 500.0 pounds per square inch **Inside Surface Condition:** Smooth

Measuring Method And Length:

6.0 feet excluding end fittings

Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-01-439-7329

Nonmetallic Hose Assembly - Page 2 of 2



	•		
I hread	Series	Designator:	

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0