Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-440-1539

C	Cross Sectional Shape:
F	Round
٦	Fhread Class:
З	3b 1st end
٦	Fhread Direction:
F	Right-hand 1st end
I	nside Diameter:
C	).391 inches
٦	Cempurature Rating:
-	65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
C	Dutside Diameter:
C	).782 inches
Ν	Ainimum Inside Bending Radius:
5	5.750 inches
E	End Application:
Ν	Aissile, minuteman Igm-30
C	Connection Style:
S	Swivel nut flare 1st end
E	End Connection Design:
S	Straight 1st end
C	Connection Type:
٦	Fhreaded internal tube 1st end
E	Burst Test Pressure:
1	4000.0 pounds per square inch
L	ayer Composition And Location:
C	Duter layer braided corrosion resistant steel wire
N	Maximum Operating Pressure:
3	3000.0 pounds per square inch
٦	Thread Size:
C	0.750 inches 1st end
ŝ	Seat Angle:
3	36.0 degrees 1st end
ŀ	Hydrostatic Test Pressure:
6	000.0 pounds per square inch
I	nside Surface Condition:
S	Smooth
N	Neasuring Method And Length:
1	02.000 inches working
٦	Thread Series Designator:
ι	Jnf 1st end
S	Shelf Life:
١	N/a

## NSN 4720-01-440-1539

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0