NSN 4720-01-440-6918

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-440-6918

Inside Diameter:				
0.750 inches				
Tempurature Rating:				
-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response				
Outside Diameter:				
1.210 inches				
Minimum Inside Bending Radius:				
9.500 inches				
End Application:				
Cover, hatch; strategic sealift conversion ships class				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 2nd end				
Connection Type:				
Threaded internal tube 1st end				
Thready Qty Per Inch (tpi):				
12 2nd end				
Burst Test Pressure:				
16000.0 pounds per square inch				
Layer Composition And Location:				
Outer layer molded rubber, synthetic				
Maximum Operating Pressure:				
4000.0 pounds per square inch				
Thread Size:				
1.312 inches 2nd end				
Seat Angle:				
37.0 degrees 2nd end				
Outer Covering Environmental Protection:				
Oil resistant and weatherproof				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
30.000 inches				
Media For Which Designed:				
Fuel/oil, hydrocarbon single response and hydraulic fluid, water base single response				

NSN 4720-01-440-6918

Nonmetallic Hose Assembly - Page 2 of 2



_	brood	Carias	Docionatori
ı	meau	oenes	Designator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0