Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-440-6932

Cross Sectional Shape: Round Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.750 inches Tempurature Rating: -40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response Outside Diameter: 1.210 inches Minimum Inside Bending Radius: 9.500 inches End Application: Cover, hatch; strategic sealift conversion ships class Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Cty Per Inch (tpi): 12 1st end Burst Test Pressure: 16000.0 pounds per square inch
Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.750 inches Tempurature Rating: -40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response Outside Diameter: 1.210 inches Minimun Inside Bending Radius: 9.500 inches End Application: Cover, hatch; strategic sealift conversion ships class Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Denection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure:
3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.750 inches Tempurature Rating: -40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response Outside Diameter: 1.210 inches Minimun Inside Bending Radius: 9.500 inches End Application: Conver, hatch; strategic sealift conversion ships class Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure:
Thread Direction: Right-hand 1st end Inside Diameter: 0.750 inches Tempurature Rating: -40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response Outside Diameter: 1.210 inches Minimum Inside Bending Radius: 9.500 inches End Application: Cover, hatch; strategic sealift conversion ships class Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Eust Test Pressure:
Right-hand 1st end Inside Diameter: 0.750 inches Tempurature Rating: -40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response Outside Diameter: 1.210 inches Minimum Inside Bending Radius: 9.500 inches End Application: Cover, hatch; strategic sealift conversion ships class Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure:
Inside Diameter: 0.750 inches Tempurature Rating: -40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response Outside Diameter: 1.210 inches Minimum Inside Bending Radius: 9.500 inches End Application: Cover, hatch; strategic sealift conversion ships class Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure:
0.750 inches0.750 inchesTempurature Rating:-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single responseOutside Diameter:1.210 inchesMinimum Inside Bending Radius:9.500 inchesEnd Application:Cover, hatch; strategic sealift conversion ships classConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endThreaded internal tube 1st endEntready Qty Per Inch (tpi):12 1st endBurst Test Pressure:
Tempurature Rating: -40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response Outside Diameter: 1.210 inches Minimum Inside Bending Radius: 9.500 inches End Application: Cover, hatch; strategic sealift conversion ships class Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure:
-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response Outside Diameter: 1.210 inches Minimum Inside Bending Radius: 9.500 inches End Application: Cover, hatch; strategic sealift conversion ships class Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Straight 1st end Connection Type: Threaded internal tube 1st end Threaded internal tube 1st end
Outside Diameter:1.210 inchesMinimum Inside Bending Radius:9.500 inchesEnd Application:Cover, hatch; strategic sealift conversion ships classConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endThreaded internal tube 1st endEnd Connection Type:12 1st endBurst Test Pressure:
1.210 inches Minimum Inside Bending Radius: 9.500 inches End Application: Cover, hatch; strategic sealift conversion ships class Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Threaded internal tube 1st end Itreaded internal tube 1st end Harst Test Pressure:
Minimum Inside Bending Radius:9.500 inchesEnd Application:Cover, hatch; strategic sealift conversion ships classConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endThready Qty Per Inch (tpi):12 1st endBurst Test Pressure:
9.500 inches End Application: Cover, hatch; strategic sealift conversion ships class Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure:
End Application:Cover, hatch; strategic sealift conversion ships classConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endThready Qty Per Inch (tpi):12 1st endBurst Test Pressure:
Cover, hatch; strategic sealift conversion ships class Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure:
Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure:
Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure:
End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure:
Straight 1st end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure:
Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure:
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure:
Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure:
12 1st end Burst Test Pressure:
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outer Covering Environmental Protection:
Oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
25.000 inches
Media For Which Designed:

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0