

View Online at <https://aerobasegroup.com/nsn/4720-01-440-7482>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

2.0 millimeters

Temperature Rating:

22.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Outside Diameter:

5.0 millimeters

Minimum Inside Bending Radius:

20.0 millimeters

End Application:

Hatch cover; strategic sealift conversion ships class; t-akr 296/298

Connection Style:

Plain optional end 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

27000.0 pounds per square inch

Layer Composition And Location:

Outer layer woven polyamide cord

Maximum Operating Pressure:

9000.0 pounds per square inch

Thread Size:

0.250 inches 2nd end

Thread Pitch In Millimeters:

2.000 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

40.000 inches working

Thread Tolerance Class:

6h internal 1st end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Npt 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0