Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-441-9371

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
Between 0.401 inches and 0.43	7 inches
Tempurature Rating:	
-35.0 degrees celsius and 120.	0 degrees celsius single response
Outside Diameter:	
Between 0.875 inches and 0.93	8 inches
End Application:	
3930-01-417-2886	
Connection Style:	
Swivel nut, gasket seal 2nd end	t the second
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
1750.0 pounds per square inch	
Layer Composition And Loca	tion:
1st layer spirally laid polyamide	cord and 2nd layer spirally laid polyamide cord and outer layer molded rubber, ethylene propylen
Thread Size:	
0.750 inches 2nd end	
Flow Angle:	
90.0 degrees 2nd end	
Inside Surface Condition:	
Smooth	
Measuring Method And Lengt	:h:
33.688 inches working	
Media For Which Designed:	
Fuel/oil, hydrocarbon single res	sponse
Thread Series Designator:	
Unf 2nd end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

## NSN 4720-01-441-9371

Nonmetallic Hose Assembly - Page 2 of 2

**Fiig:** A542a0

