NSN 4720-01-442-2306



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-442-2306 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.312 inches **Tempurature Rating:** -22.0 degrees fahrenheit and 248.0 degrees fahrenheit single response **Outside Diameter:** 0.620 inches **Minimum Inside Bending Radius:** 2.000 inches Angle Between Rigid Elbow Fittings In Deg: 30.0 **End Application:** W/SC-OD-E,T-RUCK **Connection Style:** Swivel nut, gasket seal 1st end **End Connection Design:** Elbow 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 2500.0 pounds per square inch **Layer Composition And Location:** 1st layer braided polyamide cord and outer layer molded rubber, chloroprene **Maximum Operating Pressure:** 500.0 pounds per square inch **Thread Size:**

0.625 inches 1st end

Hydrostatic Test Pressure:

1000.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

94.000 inches working

Thread Series Designator:

Unf 1st end

NSN 4720-01-442-2306

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0