

View Online at <https://aerobasegroup.com/nsn/4720-01-442-2732>

**Cross Sectional Shape:**

Round

**Thread Class:**

2a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.625 inches

**Temperature Rating:**

-22.0 degrees fahrenheit and 248.0 degrees fahrenheit single response

**Outside Diameter:**

0.960 inches

**Minimum Inside Bending Radius:**

4.500 inches

**Angle Between Rigid Elbow Fittings In Deg:**

0.0

**End Application:**

W/SC-OD-E,T-RUCK

**Connection Style:**

Plain 2nd end

**End Connection Design:**

Elbow 2nd end

**Connection Type:**

Threaded external tube 2nd end

**Thready Qty Per Inch (tpi):**

18 2nd end

**Burst Test Pressure:**

2500.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided polyamide cord and outer layer molded rubber, chloroprene

**Maximum Operating Pressure:**

500.0 pounds per square inch

**Thread Size:**

0.875 inches 2nd end

**Hydrostatic Test Pressure:**

1000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

11.110 inches working

**Thread Series Designator:**

Uns 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0