Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-442-3927

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.219 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.250 inches
End Application:
W/s code, engine, aircraft t-700 (h-60)
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Connection Type:
Threaded internal tube 1st end
Second End Relationship With First End:
Not identical
Burst Test Pressure:
16000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire err-100
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth

NSN 4720-01-442-3927

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 20.000 inches working Second End Swivel Action Capability: Not included **Special Features:** Inner conveying tube material-plastic, tetrafluoroethylene **Thread Series Designator:** Unjf 1st end Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0