Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-443-0547

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.250 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit	and 300.0 degrees fahrenheit single response
Outside Diameter:	
0.438 inches	
Minimum Inside Bending	I Radius:
2.000 inches	
End Application:	
W/s code, engine, aircrat	t t-400
Connection Style:	
Swivel nut flare 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st	end
Features Provided:	
Reusable end fittings	
Burst Test Pressure:	
6000.0 pounds per square	inch
Layer Composition And	Location:
1st layer braided corrosior	resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire
Maximum Operating Pre	ssure:
1000.0 pounds per square	inch
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 2nd end	
Hydrostatic Test Pressu	re:
3000.0 pounds per square	inch
Flow Angle:	
90.0 degrees 2nd end	
Inside Surface Conditior	
Smooth	
Measuring Method And	_ength:
44.000 inches working	



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Specification Data:

81349-mil-h-83796/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0