Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-443-3255

Cross S	ectional Shape:
Round	
Thread	Class:
3b 1st e	nd
Thread	Direction:
Right-ha	ind 1st end
Inside [	Diameter:
0.360 in	ches
Tempur	ature Rating:
-55.0 de	grees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside	Diameter:
0.550 in	ches
Minimu	m Inside Bending Radius:
0.750 in	ches
Angle E	etween Rigid Elbow Fittings In Deg:
90.0	
End Ap	plication:
Aircraft,	airlifter c-17a
Connec	tion Style:
Swivel r	ut, gasket seal 1st end
End Co	nnection Design:
Elbow 1	st end
Connec	tion Type:
Threade	d internal tube 1st end
Feature	s Provided:
Nuts dri	led for lockwire
Thready	v Qty Per Inch (tpi):
18 1st e	nd
Burst T	est Pressure:
200.0 po	ounds per square inch
Maximu	m Operating Pressure:
50.0 pot	inds per square inch
Thread	Size:
0.562 in	ches 1st end
Flow Ar	ngle:
90.0 deg	grees 1st end
Inside S	Surface Condition:
Convolu	ted
Measur	ing Method And Length:
12.500 i	nches working
Thread	Series Designator:
Unj 1st	end

## NSN 4720-01-443-3255

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

