Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-443-4597

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.500 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit ar	nd 300.0 degrees fahrenheit single response
Outside Diameter:	
0.688 inches	
Minimum Inside Bending	Radius:
2.000 inches	
End Application:	
W/s code, engine, aircraft	-400
Connection Style:	
Swivel nut flare 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st e	nd
Features Provided:	
Reusable end fittings	
Burst Test Pressure:	
6000.0 pounds per square i	nch
Layer Composition And L	ocation:
1st layer braided corrosion	esistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire
Maximum Operating Press	sure:
1000.0 pounds per square i	nch
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 2nd end	
Hydrostatic Test Pressure	:
3000.0 pounds per square i	nch
Flow Angle:	
90.0 degrees 2nd end	
Inside Surface Condition:	
Smooth	
Measuring Method And Le	ngth:
78.000 inches working	

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Specification Data:

81349-mil-h-83796/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0