## NSN 4720-01-444-2441

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end Inside Diameter: 0.750 inches

**Tempurature Rating:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-444-2441

35.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

| Outside Diameter:                                     |
|---|
| 1.160 inches  |
| Minimum Inside Bending Radius:                        |
| 5.000 inches  |
| Exterior Color:                                       |
| Green   |
| End Application:                                      |
| Strategic sealift conversion ships class              |
| Connection Style:                                     |
| Swivel nut flare 1st end                              |
| End Connection Design:                                |
| Straight 1st end                                      |
| End Fitting Component And Material:                   |
| Complete fitting stainless steel all ends             |
| Fitting Component And Surface Treatment:              |
| Complete fitting passivate 1st end                    |
| Connection Type:                                      |
| Threaded internal tube 1st end                        |
| Thready Qty Per Inch (tpi):                           |
| 12 1st end  |
| Second End Relationship With First End:               |
| Identical   |
| Burst Test Pressure:                                  |
| 800.0 pounds per square inch                          |
| First End Swivel Action Capability:                   |
| Not included  |
| Layer Composition And Location:                       |
| Outer layer molded rubber, ethylene propylene err-100 |
| Maximum Operating Pressure:                           |
| 200.0 pounds per square inch                          |
| Thread Size:  |
| 1.062 inches 1st end                                  |
|   |

## NSN 4720-01-444-2441

Nonmetallic Hose Assembly - Page 2 of 2



| Seat Angle:                  |
|------------------------------|
| 37.0 degrees 1st end         |
| Hydrostatic Test Pressure:   |
| 400.0 pounds per square inch |
| Inside Surface Condition:    |
| Smooth                       |
| Measuring Method And Length  |
| 8.250 inches                 |
| Thread Series Designator:    |
| Unj 1st end                  |
| Shelf Life:                  |
| N/a                          |
| Unit Of Measure:             |
|                              |
| Demilitarization:            |
|                              |

No Fiig: A542a0