## NSN 4720-01-444-5475

**Cross Sectional Shape:** 

Unjf 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-444-5475

| Round   |
|---|
| Thread Class:   |
| 3b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.312 inches  |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.437 inches  |
| Minimum Inside Bending Radius:  |
| 2.500 inches  |
| End Application:  |
| W/s code, aircraft, b-2 bomber  |
| Connection Style:   |
| Swivel nut, flareless 2nd end   |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Burst Test Pressure:  |
| 800.0 pounds per square inch  |
| Layer Composition And Location:   |
| Outer layer braided corrosion resistant steel wire                                    |
| Maximum Operating Pressure:   |
| 200.0 pounds per square inch  |
| Thread Size:  |
| 0.562 inches 2nd end  |
| Seat Angle:   |
| 12.0 degrees 2nd end  |
| Hydrostatic Test Pressure:  |
| 400.0 pounds per square inch  |
| Flow Angle:   |
| 45.0 degrees 2nd end  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 12.375 inches working   |
| Thread Series Designator:   |

## NSN 4720-01-444-5475

Nonmetallic Hose Assembly - Page 2 of 2



| _  |   |   |    |    |    |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
|    |   |   |    |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0