## NSN 4720-01-445-1809

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-445-1809 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.188 inches **Tempurature Rating:** -67.0 degrees fahrenheit single response **Outside Diameter:** 0.312 inches **Minimum Inside Bending Radius:** 2.000 inches **Exterior Color:** Natural **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Electrostatic discharge capability **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 1500.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 3000.0 pounds per square inch **Outer Covering Environmental Protection:** Corrosion resistant **Vacuum In Torr:** 50.8 **Inside Surface Condition:** 

Smooth

## NSN 4720-01-445-1809

Nonmetallic Hose Assembly - Page 2 of 2



## **Measuring Method And Length:**

72.000 inches working

## **Special Features:**

Hose assembly ms8000e720a, come with 5340-01-338-8543 plug, and 5975-00-944 1499 strap, use on fuel pump inlet, fms unique/wr-alc

**Thread Series Designator:** 

Unjf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0