

View Online at <https://aerobasegroup.com/nsn/4720-01-445-4394>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.188 inches

**Temperature Rating:**

-67.0 degrees fahrenheit single response

**Outside Diameter:**

0.312 inches

**Minimum Inside Bending Radius:**

2.000 inches

**Exterior Color:**

Natural

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Electrostatic discharge capability

**Burst Test Pressure:**

12000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Corrosion resistant

**Vacuum In Torr:**

50.8

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

12.000 inches working

**Special Features:**

Same as ms8000e1200a, comes with 5340-01-338-8543 plug, and 5975-00-944-1499 strap, use on disengage disconnect, fms unique wr-alc

**Thread Series Designator:**

Unjf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0