

View Online at <https://aerobasegroup.com/nsn/4720-01-445-8757>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.875 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

**Outside Diameter:**

1.109 inches

**Minimum Inside Bending Radius:**

7.380 inches

**Exterior Color:**

Natural

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Electrostatic discharge capability and reusable end fittings

**Thready Qty Per Inch (tpi):**

12 1st end

**Burst Test Pressure:**

5000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1250.0 pounds per square inch

**Thread Size:**

1.312 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

2500.0 pounds per square inch

**Outer Covering Environmental Protection:**

Corrosion resistant

**Vacuum In Torr:**

50.8

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

114.000 inches working

**Special Features:**

Drawing name hose assembly, test set, jet fuel starter/central gearbox. Same as ms8000m1140a, comes with 5340-00-804-1253 plug and 5975-00-944-1499 strap. Fms unique wr-alc, use on amad water brake

**Thread Series Designator:**

Un 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0