NSN 4720-01-446-1535

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

15.875 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-446-1535

Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.250 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response				
Outside Diameter:				
0.510 inches				
Minimum Inside Bending Radius:				
1.500 inches				
End Application:				
Aircraft, airlifter, c-17a				
Connection Style:				
Swivel nut, flareless 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Features Provided:				
Nuts drilled for lockwire				
Burst Test Pressure:				
16000.0 pounds per square inch				
Layer Composition And Location:				
Outer layer braided fiber				
Maximum Operating Pressure:				
4000.0 pounds per square inch				
Thread Size:				
0.438 inches 1st end				
Seat Angle:				
12.0 degrees 1st end				
Hydrostatic Test Pressure:				
8000.0 pounds per square inch				
Outer Covering Environmental Protection:				
Light resistant and abrasion resistant				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				

NSN 4720-01-446-1535

Nonmetallic Hose Assembly - Page 2 of 2



-	laa a al	C!	D!	_4
ı	nread	Series	Design	ator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0