

View Online at <https://aerobasegroup.com/nsn/4720-01-446-1535>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response

Outside Diameter:

0.510 inches

Minimum Inside Bending Radius:

1.500 inches

End Application:

Aircraft, airlifter, c-17a

Connection Style:

Swivel nut, flareless 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Nuts drilled for lockwire

Burst Test Pressure:

16000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided fiber

Maximum Operating Pressure:

4000.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

12.0 degrees 1st end

Hydrostatic Test Pressure:

8000.0 pounds per square inch

Outer Covering Environmental Protection:

Light resistant and abrasion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

15.875 inches

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0