## NSN 4720-01-446-7541

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-446-7541

Cross Sectional Shape:		
Round		
Thread Class:		
2b 1st end		
Thread Direction:		
Right-hand 1st end		
Inside Diameter:		
0.375 inches		
Tempurature Rating:		
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response		
Outside Diameter:		
0.750 inches		
Minimum Inside Bending Radius:		
5.000 inches		
End Application:		
Used on the m9 ace		
Connection Style:		
Swivel nut flare 1st end		
End Connection Design:		
Straight 1st end		
Connection Type:		
Threaded internal tube 1st end		
Burst Test Pressure:		
16000.0 pounds per square inch		
Layer Composition And Location:		
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic		
Maximum Operating Pressure:		
4000.0 pounds per square inch		
Thread Size:		
0.562 inches 1st end		
Seat Angle:		
37.0 degrees 1st end		
Hydrostatic Test Pressure:		
8000.0 pounds per square inch		
Outer Covering Environmental Protection:		
Cold resistant and fuel resistant and hydraulic solution resistant and oil resistant and ozone resistant and weatherproof		
Inside Surface Condition:		
Smooth		
Measuring Method And Length:		
66.000 inches		
Media For Which Designed:		
Fuel/oil, hydrocarbon single response		

## NSN 4720-01-446-7541

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Designator:

Unjf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0