

Nonmetallic Hose Assembly - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4720-01-447-1407
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.770 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 460.0 degrees fahrenheit single response
Outside Diameter:
Between 0.750 inches and 1.090 inches
Minimum Inside Bending Radius:
2.000 inches
End Application:
1430-01-418-4396
Connection Style:
Swivel nut flare 1st end
End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

3600.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1000.00 pounds per square inch

Thread Size:

1.0625 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

1800.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Convoluted

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 66.000 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unj 1st end Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A542a0