NSN 4720-01-447-1501

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-447-1501

| Right-hand 1st end |
|---|
| Inside Diameter: |
| 0.770 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 460.0 degrees fahrenheit single response |
| Outside Diameter: |
| Between 0.750 inches and 1.090 inches |
| Minimum Inside Bending Radius: |
| 2.000 inches |
| End Application: |
| 1430-01-418-4396 |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Electrostatic discharge capability |
| Thready Qty Per Inch (tpi): |
| 12 1st end |
| Burst Test Pressure: |
| 3600.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 1000.0 pounds per square inch |
| Thread Size: |
| 1.0625 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 1800.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Corrosion resistant |
| Inside Surface Condition: |
| Convoluted |

NSN 4720-01-447-1501

Nonmetallic Hose Assembly - Page 2 of 2



| Measuring Method And Length: |
|---------------------------------------|
| 39.000 inches working |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Unj 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A542a0