NSN 4720-01-447-1519

Cross Sectional Shape:

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-447-1519

3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.985 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 460.0 degrees fahrenheit single response
Outside Diameter:
Between 1.000 inches and 1.310 inches
Minimum Inside Bending Radius:
3.000 inches
End Application:
1430-01-418-4396
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
3600.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
1.312 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
1800.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Convoluted

NSN 4720-01-447-1519

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
26.000 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unj 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0