Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-447-5114

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 3b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.380 inches  |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response   |
| Outside Diameter:   |
| 0.630 inches  |
| Minimum Inside Bending Radius:  |
| 3.000 inches  |
| End Application:  |
| Seawolf class ssn   |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Burst Test Pressure:  |
| 1000.0 pounds per square inch   |
| Layer Composition And Location:   |
| 1st layer braided textile yarn and outer layer molded rubber, synthetic |
| Maximum Operating Pressure:   |
| 250.0 pounds per square inch  |
| Thread Size:  |
| 0.750 inches 1st end  |
| Seat Angle:   |
| 45.0 degrees 1st end  |
| Hydrostatic Test Pressure:  |
| 500.0 pounds per square inch  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 96.000 inches   |
| Media For Which Designed:   |
| Fuel/oil, hydrocarbon single response                                   |
| Thread Series Designator:   |
| Unjf 1st end  |

## NSN 4720-01-447-5114

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

