Nonmetallic Hose Assembly - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/4720-01-447-6182



F	Round
	Fhread Class:
	a 2nd end
т	Thread Direction:
F	Right-hand 1st end
т	Fempurature Rating:
-/	40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response
N	Ainimum Inside Bending Radius:
5	5.000 inches
E	End Application:
т	Fruck, family of medium tactical vehicle (fmtv)-light
C	Connection Style:
S	Swivel nut flare 1st end
E	End Connection Design:
S	Straight 2nd end
C	Connection Type:
Т	Fhreaded internal pipe 1st end
E	Burst Test Pressure:
1	200.0 pounds per square inch
N	Naximum Operating Pressure:
3	300.0 pounds per square inch
Т	Thread Size:
0	0.750 inches 1st end
S	Seat Angle:
3	37.0 degrees 1st end
h	nside Surface Condition:
S	Smooth
N	Measuring Method And Length:
1	87.0 millimeters and 213.0 millimeters
Т	Thread Series Designator:
ι	Jnf 1st end
S	Shelf Life:
Ν	N/a
ι	Jnit Of Measure:
	-
C	Demilitarization:
Ν	No
F	-iig:
Α	A542a0