Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-448-1214

| Cross Sectional Shape: | |
|--|--|
| Round | |
| Thread Class: | |
| 3b 1st end | |
| Thread Direction: | |
| Right-hand 1st end | |
| Inside Diameter: | |
| 0.438 inches | |
| Tempurature Rating: | |
| -65.0 degrees fahrenheit and 275.0 de | egrees fahrenheit single response |
| Outside Diameter: | |
| 0.641 inches | |
| Minimum Inside Bending Radius: | |
| 4.000 inches | |
| End Application: | |
| Used on weapon system aircraft, b-2 b | pomber |
| Connection Style: | |
| Swivel nut flare 2nd end | |
| End Connection Design: | |
| Straight 1st end | |
| Connection Type: | |
| Threaded internal tube 1st end | |
| Features Provided: | |
| Reusable end fittings | |
| Burst Test Pressure: | |
| 5600.0 pounds per square inch | |
| Layer Composition And Location: | |
| 1st layer braided corrosion resistant st | teel wire, partial coverage and outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: | |
| 1400.0 pounds per square inch | |
| Thread Size: | |
| 0.750 inches 2nd end | |
| Seat Angle: | |
| 37.0 degrees 2nd end | |
| Hydrostatic Test Pressure: | |
| 2100.0 pounds per square inch | |
| Flow Angle: | |
| 45.0 degrees 2nd end | |
| Inside Surface Condition: | |
| Smooth | |
| Measuring Method And Length: | |
| 20.500 inches | |

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A542a0