Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-448-1717

Cross Section	al Shape:
Round	
Thread Class:	
3b 1st end	
Thread Directi	on:
Right-hand 1st	end
Inside Diamete	er:
0.438 inches	
Tempurature I	Rating:
-65.0 degrees f	ahrenheit and 275.0 degrees fahrenheit single response
Outside Diamo	eter:
0.641 inches	
Minimum Insid	de Bending Radius:
4.000 inches	
End Application	on:
Used on weapo	on system aircraft, b-2 bomber
Connection St	yle:
Swivel nut flare	2nd end
End Connection	on Design:
Straight 1st end	t de la construcción de la constru
Connection Ty	ире:
Threaded inter	nal tube 1st end
Features Prov	ided:
Reusable end f	ittings
Burst Test Pre	essure:
5600.0 pounds	per square inch
Layer Compos	sition And Location:
1st layer braide	d corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire
Maximum Ope	rating Pressure:
1400.0 pounds	per square inch
Thread Size:	
0.750 inches 2	nd end
Seat Angle:	
37.0 degrees 2	nd end
Hydrostatic Te	est Pressure:
2100.0 pounds	per square inch
Flow Angle:	
45.0 degrees 2	nd end
Inside Surface	
Smooth	
Measuring Me	thod And Length:
45.500 inches	-



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A542a0