

View Online at <https://aerobasegroup.com/nsn/4720-01-448-6022>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.187 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 302.0 degrees fahrenheit single response

Outside Diameter:

0.520 inches

Minimum Inside Bending Radius:

3.000 inches

End Application:

Trolley sheav cage 53711, w/s code jt cimmaron class ao

Connection Style:

Inverted flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Connection Type:

Threaded external pipe 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

12000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer braided textile yarn err-100

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.125 inches 1st end

Seat Angle:

30.0 degrees 1st end

Vacuum In Torr:

50.800

Inside Surface Condition:

Smooth

Measuring Method And Length:

20.000 inches working

Media For Which Designed:

Air single response and water single response and hydraulic fluid single response

Thread Series Designator:

Nptf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0