Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-448-7536

ross Sectional Shape:	
lound	
hread Class:	
b 1st end	
hread Direction:	
light-hand 1st end	
nside Diameter:	
.219 inches	
empurature Rating:	
40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response	
Dutside Diameter:	
.438 inches	
linimum Inside Bending Radius:	
.000 inches	
connection Style:	
wivel nut flare 1st end	
nd Connection Design:	
traight 1st end	
connection Type:	
hreaded internal tube 1st end	
urst Test Pressure:	
.000 pounds per square inch	
ayer Composition And Location:	
st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel	wire
laximum Operating Pressure:	
000.0 pounds per square inch	
hread Size:	
.438 inches 1st end	
eat Angle:	
7.0 degrees 1st end	
lydrostatic Test Pressure:	
000.0 pounds per square inch	
nside Surface Condition:	
mooth	
leasuring Method And Length:	
2.250 inches working	
ledia For Which Designed:	
uel/oil, hydrocarbon single response	
hread Series Designator:	
Injf 1st end	
helf Life:	
l/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0