

View Online at <https://aerobasegroup.com/nsn/4720-01-449-6040>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.290 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

Outside Diameter:

0.460 inches

Minimum Inside Bending Radius:

1.250 inches

Inner Conveying Tube Style:

Annular close-pitch corrugated

End Application:

W/s code, aircraft, hercules c-130

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Identical ends

Burst Test Pressure:

4000.0 pounds per square inch

Layer Composition And Location:

1st layer molded polytetrafluoroethylene err-100

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Measuring Method And Length:

12.000 inches

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0