Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-450-0876

C	
Cross	Sectional Shape:
Round	
Thread	d Class:
2b 1st	end
Thread	d Direction:
Right-h	nand 1st end
Inside	Diameter:
0.310 i	inches
Tempu	urature Rating:
-20.0 c	degrees fahrenheit single response and 250.0 degrees fahrenheit single response
Outsic	de Diameter:
0.670 i	inches
Minim	um Inside Bending Radius:
4.000 i	inches
End A	pplication:
Hose a	assembly cage 03950; w/s code jg seawolf class ssn
Conne	ection Style:
Swivel	nut flare 1st end
End C	onnection Design:
Straigh	nt 1st end
End Fi	itting Component And Material:
Compl	ete fitting copper alloy all ends
Conne	ection Type:
Thread	ded internal tube 1st end
Secon	d End Relationship With First End:
Identic	al
Burst	Test Pressure:
2500.0) pounds per square inch
First E	End Swivel Action Capability:
Not inc	cluded
Layer	Composition And Location:
Outer I	layer braided textile yarn err-100
Maxim	num Operating Pressure:
350.0	pounds per square inch
Thread	d Size:
0.625 i	inches 1st end
Seat A	Angle:
45.0 de	egrees 1st end
Vacuu	Im In Torr:
50.8	
Inside	Surface Condition:
Smoot	h

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 10.000 feet excluding end fittings **Special Features:** Inner conveying tube material-rubber, synthetic Media For Which Designed: Refrigerant 12 single response **Thread Series Designator:** Unf 1st end Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0