NSN 4720-01-450-1764

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-450-1764
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.000 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
1.500 inches
Minimum Inside Bending Radius:
3.000 inches
End Application:
W/s code, seal delivery vehicle
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Layer Composition And Location:
1st layer braided synthetic cord and outer layer braided polyamide cord
Maximum Operating Pressure:
135.0 pounds per square inch
Thread Size:
1.438 inches 1st end
Criticality Code Justification:
Zzzy
Inside Surface Condition:
Smooth
Measuring Method And Length:
52.250 inches
Thread Series Designator:
Un 1st end
Reference Number Differentiating Characteristics:
Material controlled iaw ss800-ag-man-010/p9290 system certification procedures and criteria manual for deep submergence systems and
requires cleaning, packing, and marking iaw mil-std-1622 or mil-std-1330 as deemed applicable; critical item for safety and survival of deep

N/a

Shelf Life:

submergence research and rescue vehicals as differentiated by special test features

NSN 4720-01-450-1764

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0