Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-450-4621

| Cross Sectional Shape: |
|---|
| Round |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.500 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.750 inches |
| Minimum Inside Bending Radius: |
| 5.000 inches |
| End Application: |
| 4930-01-139-2492; vehicle, aircraft refueler r-14 |
| Connection Style: |
| Plain 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external pipe 1st end |
| Burst Test Pressure: |
| 1200.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided fiber and outer layer molded rubber, chloroprene |
| Maximum Operating Pressure: |
| 200.0 pounds per square inch |
| Thread Size: |
| 0.750 inches 1st end |
| Outer Covering Environmental Protection: |
| Oil resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 16.0 feet excluding end fittings |
| Special Features: |
| Second end 0.500 in. Gate valve |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 4720-01-450-4621

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

