NSN 4720-01-450-9720

Nonmetallic Hose Assembly - Page 1 of 2



view Online at https://aerobasegroup.com/hsn/4720-01-450-9720
Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-55.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response
Outside Diameter:
0.484 inches
Minimum Inside Bending Radius:
2.000 inches
Hose Or Tubing Specification/std Data:
Mil-h-13444, type 3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
First End Fitting Specification/std Data:
Sae j516, table 4e, 4-4 250146 standard (includes industry or association standards, individual manufactureer standards, etc.).
End Application:
M9 ace vehicle
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting steel all ends
Fitting Component And Surface Treatment:
Complete fitting zinc 1st end
Connection Type:
Threaded internal tube 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
6000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer braided textile yarn err-100
Maximum Operating Pressure:

0.438 inches 1st end

Thread Size:

1500.0 pounds per square inch

NSN 4720-01-450-9720

Nonmetallic Hose Assembly - Page 2 of 2



Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
3000.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
6.000 inches	
Special Features:	
Inner conveying tube material-rubber, synthetic	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response and water single response and air single response	
Thread Series Designator:	
Unf 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	
A542a0	
Mil-std (military Standard):	
Mil-h-13444 spec.	