NSN 4720-01-450-9720

Nonmetallic Hose Assembly - Page 1 of 2



| view Online at https://aerobasegroup.com/hsn/4720-01-450-9720 |
|--|
| Cross Sectional Shape: |
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.188 inches |
| Tempurature Rating: |
| -55.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.484 inches |
| Minimum Inside Bending Radius: |
| 2.000 inches |
| Hose Or Tubing Specification/std Data: |
| Mil-h-13444, type 3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| First End Fitting Specification/std Data: |
| Sae j516, table 4e, 4-4 250146 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| End Application: |
| M9 ace vehicle |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| End Fitting Component And Material: |
| Complete fitting steel all ends |
| Fitting Component And Surface Treatment: |
| Complete fitting zinc 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Second End Relationship With First End: |
| Identical |
| Burst Test Pressure: |
| 6000.0 pounds per square inch |
| First End Swivel Action Capability: |
| Not included |
| Layer Composition And Location: |
| 1st layer braided textile yarn err-100 |
| Maximum Operating Pressure: |

0.438 inches 1st end

Thread Size:

1500.0 pounds per square inch

NSN 4720-01-450-9720

Nonmetallic Hose Assembly - Page 2 of 2



| Seat Angle: | |
|---|--|
| 37.0 degrees 1st end | |
| Hydrostatic Test Pressure: | |
| 3000.0 pounds per square inch | |
| Inside Surface Condition: | |
| Smooth | |
| Measuring Method And Length: | |
| 6.000 inches | |
| Special Features: | |
| Inner conveying tube material-rubber, synthetic | |
| Media For Which Designed: | |
| Fuel/oil, hydrocarbon single response and water single response and air single response | |
| Thread Series Designator: | |
| Unf 1st end | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| - | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A542a0 | |
| Mil-std (military Standard): | |
| Mil-h-13444 spec. | |
| | |