## NSN 4720-01-451-2877

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

**Thread Direction:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-451-2877

Right-hand 1st end
Inside Diameter:
0.280 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 460.0 degrees fahrenheit single response
Outside Diameter:
0.465 inches
Minimum Inside Bending Radius:
0.500 inches
End Application:
NSN1-43-001-4184
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
4000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Convoluted
Measuring Method And Length:
15.000 inches
Thread Series Designator:
Unjf 1st end

## NSN 4720-01-451-2877

Nonmetallic Hose Assembly - Page 2 of 2



Shelf	Life:
•	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0