## NSN 4720-01-451-4085



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-451-4085 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.810 inches **Minimum Inside Bending Radius:** 2.000 inches **Exterior Color:** Orange **End Application:** Motor propuls cage 60089; w/s code ka usns stalwart class tagos **Connection Style:** Inverted flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external pipe 1st end **Burst Test Pressure:** 14000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided polyamide cord and outer layer molded polyurethane **Maximum Operating Pressure:** 3500.0 pounds per square inch **Thread Size:** 0.500 inches 1st end Seat Angle: 30.0 degrees 1st end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 36.000 inches excluding end fittings **Thread Series Designator:** Npt 1st end Shelf Life: N/a

**Unit Of Measure:** 

## NSN 4720-01-451-4085

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0