NSN 4720-01-451-7377

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-451-7377

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.380 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.690 inches |
| Minimum Inside Bending Radius: |
| 5.000 inches |
| End Application: |
| 3930-01-417-2886 |
| Connection Style: |
| Swivel nut flare 2nd end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 9000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided steel wire and outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 2250.0 pounds per square inch |
| Thread Size: |
| 0.750 inches 1st end |
| Seat Angle: |
| 37.0 degrees 2nd end |
| Hydrostatic Test Pressure: |
| 4500.0 pounds per square inch |
| Flow Angle: |
| 45.0 degrees 2nd end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 96.000 inches |
| Media For Which Designed: |

Fuel/oil, hydrocarbon single response

NSN 4720-01-451-7377

Nonmetallic Hose Assembly - Page 2 of 2



| Thread S | eries De | signator: |
|----------|----------|-----------|
|----------|----------|-----------|

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0