NSN 4720-01-451-7800

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-451-7800

Cross Sectional Shape:			
Round			
Thread Class:			
3b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.380 inches			
Tempurature Rating:			
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response			
Outside Diameter:			
0.690 inches			
Minimum Inside Bending Radius:			
5.000 inches			
End Application:			
USED-ON-NSN-3930			
Connection Style:			
Swivel nut flare 2nd end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Burst Test Pressure:			
9000.0 pounds per square inch			
Layer Composition And Location:			
1st layer braided wire and outer layer molded rubber, synthetic			
Maximum Operating Pressure:			
2250.0 pounds per square inch			
Thread Size:			
0.562 inches 2nd end			
Seat Angle:			
37.0 degrees 2nd end			
Hydrostatic Test Pressure:			
4500.0 pounds per square inch			
Flow Angle:			
90.0 degrees 2nd end			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
72.000 inches working			
Media For Which Designed:			

Fuel/oil, hydrocarbon single response

NSN 4720-01-451-7800

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:
	0000	_00.9.	

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0