

View Online at <https://aerobasegroup.com/nsn/4720-01-452-2307>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 110.0 degrees fahrenheit single response

Outside Diameter:

0.580 inches

Minimum Inside Bending Radius:

0.750 inches

Exterior Color:

Green

First End Fitting Specification/std Data:

Mil-t-8506 standard (includes industry or association standards, individual manufactureer standards, etc.).

End Application:

C 17a aircraft cage 88277; w/s code dt aircraft, airlifter c-17a

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting steel comp 304 all ends

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

1200.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer braided textile yarn err-100

Maximum Operating Pressure:

300.0 pounds per square inch

Thread Size:

0.500 inches 1st end

Seat Angle:

37.0 degrees 1st end

Inside Surface Condition:

Convuluted

Measuring Method And Length:

19.000 inches working

Special Features:

Inner conveying tube material-plastic, polytetrafluoroethylene

Media For Which Designed:

Oxygen, gaseous single response

Thread Series Designator:

Unjf 1st end

Specification Data:

Mil-t-8506 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-t-8506 spec.