Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-453-7311

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.750 inches

Tempurature Rating:

-40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response

Outside Diameter:

1.160 inches

Minimum Inside Bending Radius:

9.500 inches

Hose Or Tubing Specification/std Data:

Sae100r2at specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

End Application:

Connection Style:

2320-01-442-1940 cage 45152

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Threaded internal tube 2nd end

Thready Qty Per Inch (tpi):

12 2nd end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

12400.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, synthetic err-100

Maximum Operating Pressure:

3100.0 pounds per square inch

Thread Size:

1.3125 inches 1st end

Seat Angle:

37.0 degrees 2nd end



Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
72.000 inches
Second End Swivel Action Capability:
Not included
Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:
Air single response and water single response and fuel/oil, hydrocarbon single response
Thread Series Designator:
Un 2nd end
Specification Data:
Sae100r2at professional/industrial association specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0