## NSN 4720-01-453-7345

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-453-7345

Cross Sectional Shape:						
Round						
Thread Class:						
3b 1st end						
Thread Direction:						
Right-hand 1st end						
Inside Diameter:						
0.750 inches						
Tempurature Rating:						
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response						
Outside Diameter:						
1.160 inches						
Minimum Inside Bending Radius:						
9.500 inches						
End Application:						
2320-01-442-1940 cage 45152						
Connection Style:						
Swivel nut flare 2nd end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 2nd end						
Thready Qty Per Inch (tpi):						
12 2nd end						
Burst Test Pressure:						
12400.0 pounds per square inch						
Layer Composition And Location:						
2nd layer braided steel wire and 3rd layer braided steel wire and outer layer molded rubber, synthetic						
Maximum Operating Pressure:						
3100.0 pounds per square inch						
Thread Size:						
1.3125 inches 1st end						
Seat Angle:						
37.0 degrees 2nd end						
Flow Angle:						
90.0 degrees 2nd end						
Inside Surface Condition:						
Smooth						
Measuring Method And Length:						
36.000 inches						
Media For Which Designed:						

media i oi willeli besiglica.

Air and water and fuel/oil, hydrocarbon single response

## NSN 4720-01-453-7345

Nonmetallic Hose Assembly - Page 2 of 2



	••		•	_		
ı	hre	ลด	Seri	26 I I	PSIU	nator:
•		uu	CCII		COIG	mator.

Un 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0