## NSN 4720-01-453-7738

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-453-7738

Cross Sectional Shape:					
Round					
Thread Class:					
3b 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.750 inches					
Tempurature Rating:					
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response					
Outside Diameter:					
1.160 inches					
Minimum Inside Bending Radius:					
9.500 inches					
End Application:					
2320-01-442-1940 cage 45152					
Connection Style:					
Swivel nut flare 2nd end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Thready Qty Per Inch (tpi):					
12 2nd end					
Burst Test Pressure:					
12400.0 pounds per square inch					
Layer Composition And Location:					
2nd layer braided steel wire and 3rd layer braided steel wire and outer layer molded rubber, synthetic					
Maximum Operating Pressure:					
3100.0 pounds per square inch					
Thread Size:					
1.0625 inches 2nd end					
Seat Angle:					
37.0 degrees 2nd end					
Flow Angle:					
45.0 degrees 2nd end					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
46.800 inches					
Media For Which Designed					

Air and water and fuel/oil, hydrocarbon single response

## NSN 4720-01-453-7738

Nonmetallic Hose Assembly - Page 2 of 2



_		•	_	
1	hread	Series	1)66	ignator:
•	mcaa	OCI ICS	000	igilatoi.

Un 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0