## NSN 4720-01-453-7816

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-453-7816 **Cross Sectional Shape:** Round **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.625 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response **Outside Diameter:** 1.000 inches **Minimum Inside Bending Radius:** 8.000 inches **End Application:** 2320-01-442-1940 cage 45152 **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 2nd end **Burst Test Pressure:** 14500.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided steel wire and 3rd layer braided steel wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 3600.0 pounds per square inch **Thread Size:** 0.875 inches 2nd end Seat Angle: 37.0 degrees 2nd end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 67.000 inches Media For Which Designed: Air and water and fuel/oil, hydrocarbon single response **Thread Series Designator:** Unf 2nd end

Shelf Life:

N/a

## NSN 4720-01-453-7816

Nonmetallic Hose Assembly - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

A542a0