NSN 4720-01-453-9530

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-453-9530

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.880 inches
Tempurature Rating:
-55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
1.200 inches
Minimum Inside Bending Radius:
7.380 inches
End Application:
USED-ON-TRU-CK,F
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
1500.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated fabric
Maximum Operating Pressure:
375.0 pounds per square inch
Thread Size:
1.312 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
750.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
1612.9 millimeters
Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-01-453-9530

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Designator:
--------	--------	-------------

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0