

View Online at <https://aerobasegroup.com/nsn/4720-01-454-2289>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.665 inches

Temperature Rating:

-54.0 degrees celsius single response and 149.0 degrees celsius single response

Outside Diameter:

0.750 inches

Minimum Inside Bending Radius:

4.500 inches

First End Fitting Specification/std Data:

Ams4082; ams4117; ams4119 standard (includes industry or association standards, individual manufactureer standards, etc.).

End Application:

Dcn'only cage 26512

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Socket aluminum alloy 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

4000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire err-100

Unable To Decode:

Unable to decode or unable to decode

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

1.0625 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

8.875 inches

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unj 1st end

Specification Data:

Ams4082; ams4117; ams4119 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0