

View Online at <https://aerobasegroup.com/nsn/4720-01-454-4118>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.844 inches

Temperature Rating:

-54.0 degrees celsius and 149.0 degrees celsius single response

Outside Diameter:

1.000 inches

Minimum Inside Bending Radius:

5.500 inches

End Application:

Ocn'only cage 26512

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

3000.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

750.0 pounds per square inch

Thread Size:

1.3125 inches 1st end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

1500.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

29.375 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unj 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0