Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-455-5502

. .	onal Shape:
Round	
Inside Diam	
0.260 inches	
Tempuratur	
-40.0 degree	es fahrenheit and 200.0 degrees fahrenheit single response
Outside Dia	meter:
0.550 inches	
Minimum In	side Bending Radius:
3.000 inches	
End Applica	ation:
2350-01-305	5-0028; w/s code 23a, howitzer, m-109 series, self propelled
Burst Test F	Pressure:
20000.0 pou	inds per square inch
Layer Comp	position And Location:
1st layer brai	ided wire and outer layer molded rubber, synthetic
Maximum O	operating Pressure:
5000.0 poun	ds per square inch
Inside Surfa	ace Condition:
Smooth	
Measuring M	Method And Length:
18.000 inche	25
Special Feat	tures:
Recuperator	/replenisher service hose assembly; one end has end fitting p/n 12927647-1 with plug p/n 12927649; the other end has
bulkhead mo	punting quick disconnect coupling half p/n 12927669-1 with dust cap p/n 12927671
Media For W	Vhich Designed:
Hydraulic flui	id single response
Shelf Life:	
N/a	
Unit Of Mea	sure:
Demilitariza	tion:
No	
Fiig:	